



MXT-52MP3

Order No.: 0176790

PRODUCTINFOS

Mixer with integrated MP3 player,

for flush-mounting into walls.

- 2 balanced microphone/line inputs (XLR), each with gain control and selectable phantom power
- 2 line inputs (RCA L/R)
- 1 aux input (3.5 mm jack)
- Integrated MP3 player with USB port and SD/MMC card slot, including remote control
- Each input with level control
- Output with 2-way tone control and level control
- LED for indicating clip and operating status
- Metal housing with rear cover for protection against dirt

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

MXT-52MP3

No. of channels	6
No. of inputs	5
Mic input	1 mV, 2 x XLR, bal.
Line input	230 mV, 2 x XLR, bal. 160 mV, 2 x RCA L/R
Aux input	160 mV, 1 x 3.5 mm jack
Master output	1-10 V, terminal, mono, bal.
USB	yes
Frequency range	20-20,000 Hz
THD	< 0.03%
S/N ratio	> 78 dB
Equalizer bass	±10 dB/100 Hz
Equalizer treble	±10 dB/12 kHz
Phantom power	19 V
Media player	MP3, USB
Power supply	DC/~ 24 V/250 mA
Mains voltage	24 V
Admiss. ambient temp.	0-40 °C
Dimensions	200 x 160 x 90 mm
Width	200 mm
Height	160 mm
Depth	90 mm
Weight	1.25 kg
Packaging dimensions (W x H x L)	0.22 x 0.145 x 0.265 m

MXT-52MP3

Gross weight	1.53 kg
Net weight	1.276 kg

MXT-52MP3

EAN code	4007754261387
Net weight	1.276 kg