



EDL-165AB/WS



Order No.: 0163650

PRODUCTINFOS

PA A/B ceiling speaker,

with EN 54-24 certification for systems with A/B speaker distribution according to EN 60849.

- 100 V transmission technology
- 13 cm full range speaker with dual voice coil
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Metal housing with fire protection cover and protective metal front grille
- Ball-proof according to DIN 18032, Part 3

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

EDL-165AB/WS

Transmission technology	100 V
Frequency range	80-19,000 Hz
Power rating (RMS)	2 x 6/3/1.5 W
SPL	93 dB (1 W/1 m) 78 dB (EN, 1 W/4 m)
Max. rated SPL	101 dB (1 m) 86 dB (EN, 4 m)
Radiation angle, horizontal	180° (500 Hz) 180° (1 kHz) 155° (2 kHz) 76° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 180° (1 kHz) 155° (2 kHz) 76° (4 kHz)
Mounting cutout	Ø 140-150 mm
Mounting depth	90 mm
Dimensions	Ø 170 mm x 95 mm
Outside diameter	Ø 170 mm
Width	Ø 170 mm
Height	Ø 170 mm
Depth	95 mm
Colour	white, RAL9010
Admiss. ambient temp.	-10 °C to +55 °C
Weight	1.4 kg
Packing unit	1
Type of speaker	130
Packaging dimensions (W x H x L)	0.195 x 0.1 x 0.195 m
Gross weight	1.538 kg
Net weight	1.437 kg

EDL-165AB/WS

EAN code	4007754263848
Net weight	1.437 kg