



MCX-200/SW

Order No.: 0244170

PRODUCTINFOS

Electronic stereo crossover network

- Subwoofer operation/satellite operation
- Additional mono subwoofer output
- Output level can be adjusted individually for each frequency range
- Switchable phase for subwoofer output
- Adjustable crossover frequency
- Ground lift switch
- All connections via 6.3 mm jacks, unbal.

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

MCX-200/SW

Frequency range	10-30,000 Hz, -0.5 dB
Crossover frequency	60-500 Hz, 12 dB/oct.
High-pass filter	15 Hz, 12 dB/oct.
THD	< 0.03%
Inputs	6 V max./56 k Ω
Outputs	6 V max./100 Ω (± 10 dB)
S/N ratio	> 80 dB
Power supply	~ 230 V/50 Hz/5 VA
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 44.5 x 185 mm, 1 RS
Weight	2 kg

MCX-200/SW

EAN code	4007754182712
Net weight	2.185 kg