



EPS32

Order No.: 1000870

PRODUCTINFOS

Amplifier, 2 x 15 W

- For mounting onto DIN rails according to DIN EN 60529, 2 HP
- 2-channel class D amplifier
- Selectable mode stereo/bridged
- Inputs to be switched externally
- Balanced and unbalanced input
- Summing amplifier input
- Microphone input
- Separate volume control for each channel
- High-efficiency green design

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock.

Do not operate the appliance if there is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair.

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range -20 °C to $+40\text{ °C}$).

If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

TECHNICAL SPECIFICATIONS

EPS32

Peak output power	30 W
Power rating	24 W
Power rating at 4 Ω	2 x 12 W
Power rating at 8 Ω	2 x 6 W
Power rating with 4 Ω bridged operation	1 x 24 W
Power rating with 8 Ω bridged operation	1 x 12 W
Output impedance	4-8 Ω
Channels	2
Inputs	1 V/47 k Ω (bal.), 22 k Ω (unbal.)
Frequency range	42-21,000 Hz
S/N ratio	92 dB
THD	0.05%
Phantom power	9-12 V
Operating voltage (possible alternative)	DC 12-26 V, rec. DC 24 V
Admiss. ambient temp.	-20 °C to $+40\text{ °C}$
Width	36 mm
Height	101 mm
Depth	62 mm
Weight	98 g
Connections	spring-loaded terminals
Packaging dimensions (W x H x L)	0.037 x 0.095 x 0.075 m
Gross weight	0.1297 kg
Net weight	0.098 kg

EPS32

EAN code 4007754418491

Net weight 0.098 kg