



BS-120



Order No.: 1001473

PRODUCTINFOS

Ceiling cabinet PA system

for mounting on or suspending from ceilings or ceiling constructions

- High-quality transmission of speech and music
- 100 V transmission technology via audio transformer with 3 power taps 120/60/30 W
- 4 x 2-way speaker (8 cm) with additional high-range horn
- Excellent efficiency, superb sound characteristics and optimised radiation properties due to 4 speakers so that it is possible to achieve a defined directionality even within the critical mid-range
- Particularly suited for ceiling PA in surroundings with a long reverberation time, high ceilings and a high ambient noise level
- Black laquered MDF cabinet with mounting eyelets for suspension by steel cables

Manufacturer information:

PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

TECHNICAL SPECIFICATIONS

BS-120

Active/passive	passive
Transmission technology	100 V
Total power rating	120 W
Power rating (RMS)	120/60/30 W
Frequency range	80-22,000 Hz
System	2-way
Number of speakers	4
Speaker size	8 cm
SPL	102 dB/W/m
Max. rated SPL	123 dB
Radiation angle/beam angle	H85°/V85° (1 kHz)
	H60°/V60° (2 kHz)
	H50°/V50° (4 kHz)
Radiation angle, horizontal	85° (1 kHz)
	60° (2 kHz)
	50° (4 kHz)
Radiation angle, vertical	85° (1 kHz)
	60° (2 kHz)
	50° (4 kHz)
Housing material	MDF
Colour	Black, RAL 9005
Mounting device	mounting eyelets
Dimensions	500 x 500 x 300 mm
Width	500 mm
Height	500 mm
Depth	300 mm
Weight	22.5 kg
Inputs	Pressure terminals
Packaging dimensions (W x H x L)	0.6 x 0.4 x 0.45 m
Gross weight	24 kg
Net weight	23 kg
BS-120	
EAN code	4007754430066
Net weight	23 kg