



## FGA-30

Order No.: 0212430

### PRODUCTINFOS

#### Ground isolator,

compact design, for preventing signal interference and hum loops which may occur, e.g. when connecting PC sound cards or laptops to an amplifier.

- Galvanically isolated inputs and outputs
- 2 RCA jacks
- 3.5 mm stereo plug
- Input/output impedance: 20 k $\Omega$
- Frequency range: 20-30,000 Hz
- THD: < 0.01%
- Transmission ratio 1:1
- $\varnothing$  24 mm x 38 mm, 32 g
- Length including connection cable: approx. 40 cm

#### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Konsul-Smidt-Str. 68  
28217 Bremen

Germany  
info@monacor.com

### Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

## TECHNICAL SPECIFICATIONS

### FGA-30

Description	ground isolator
Frequency range	20-30,000 Hz
Input impedance	20 kΩ
Output impedance	20 kΩ
Transmission ratio	1:1
THD	< 0.01%
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 24 mm x 38 mm
Weight	31 g
Inputs	1 x RCA inline jack L/R, 1 x 3.5 mm stereo plug
Outputs	1 x RCA inline jack L/R, 1 x 3.5 mm stereo plug

### FGA-30

EAN code	4007754210064
Net weight	0.031 kg