



SUB/SW

Order No.: 1000662

PRODUCTINFOS

Subwoofer extension for Spottune speaker systems,

The Spottune SUB subwoofer is used in combination with the Spottune OMNI speakers as an addition to the Spottune speaker system. The subwoofer can be mounted either on the floor, on the wall or on the ceiling, depending on the requirements and spatial conditions. No cables are required for the connection to the central audio streamer Spottune STREAM, simply use plug-and-play.

Spottune wireless smart subwoofer,

as an addition to existing Spottune speaker systems for extending the bass reproduction.

- All-in-one smart subwoofer (built-in 200 W amplifier and receiver)
- 25 cm (10") bass speaker/driver of long excursion
- Closed cabinet design for optimum output power and extended bass reproduction
- Easy plug-and-play installation/connection to Spottune audio streamer STREAM
- Reliable and stable audio transmission in the frequency range of 1.9 GHz

Manufacturer information:

Spottune ApS

Nordre Fasanvej 113, 2. Floor
2000 Frederiksberg
Denmark
support@spottune.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never adjust the speakers to a very high volume. Permanent high volumes may damage your hearing!

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

SUB/SW

Active/passive	active
Transmission technology	wireless
Total output power	300 W
Power rating (RMS)	200 W, class D amplifier
Frequency range	20-200 Hz
Number of speakers	1
Speaker size	25 cm (10")
Max. rated SPL	100 dB
Radiation angle/beam angle	omnidirectional
Housing material	plastic
Colour	black
Admiss. ambient temp.	0-40 °C
Power supply	~ 100-240 V/50-60 Hz
Dimensions	540 x 200 x 360 mm
Width	540 mm
Height	200 mm
Depth	360 mm
Weight	12.65 kg
Inputs	mains cable
Other features	audio transmission: UHF band 1.8-1.9 GHz, operating range: approx. 50-100 m, depending on surrounding and place of application
Packaging dimensions (W x H x L)	0.48 x 0.31 x 0.66 m

SUB/SW

Gross weight 15.48 kg

Net weight 12.65 kg

SUB/SW

EAN code 5745000259007

Net weight 12.65 kg