



ADP-DAO-0X2

Order No.: 0259680

PRODUCTINFOS

Dante® analogue output adapter (2-channel)

- For connecting analogue audio line level devices (e.g. active speakers) to a Dante® audio network
- Adjustable signal level: +18/+4/0 dBu, 0/-10 dBV (via Dante® controller)
- Frequency range: 20-20,000 Hz
- Impedance: 150 kΩ (bal.), 75 kΩ (unbal.)
- Dynamic range: > 100 dB
- S/N ratio: > 100 dB
- THD: < 0.01%
- Sampling rates: 44.1/48/96 kHz, 24 bits
- Connections: 1 x RJ45, 2 x XLR plug

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Manufacturer information:

Audinate Ltd.

Future Business Centre
Kings Hedges Rd
Cambridge CB4 2HY
United Kingdom
info@audinate.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

ADP-DAO-0X2

Description	Dante® analogue output adapter
Type	2-channel
Colour	black
Power supply	PoE
Weight	165 g
Connections	1 x RJ45, 2 x 3-pole XLR plug
Packing unit	1
Packaging dimensions (W x H x L)	0.035 x 0.085 x 0.2 m
Gross weight	0.195 kg
Net weight	0.165 kg

ADP-DAO-0X2

EAN code	9353345000046
Net weight	0.165 kg

ADP-DAO-0X2

Sampling rates	44.1/48/96 kHz
Resolution	24 Bit