



ATT-1950

Order No.: 0171370

PRODUCTINFOS

6-way PA volume control for 482 mm (19") rack installation

- 6 audio transformers for 100 V transmission technology
- Power rating: 6 x 50 W
- Connection for priority circuit, 6 priority relays (DC 24 V/20 mA)
- Attenuation in 10 steps, position 0 is OFF
- Aluminium front panel
- Available in 3 power classes
- Plug-in screw terminal

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

During operation, there is a hazard of contact with a voltage of up to 100 V at the connection cables. Installation must be carried out by skilled personnel only. Make sure that the power matching is correct. An overload will damage the power amplifier and the attenuator!
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is

not harmful to the environment.

TECHNICAL SPECIFICATIONS

ATT-1950

Description	wall-mounted PA volume control
Frequency range	50-18,000 Hz
Power rating	6 x 50 W
Priority facility	yes
Dimensions	484 x 88 x 77 mm, 2 RU
Weight	1.379 kg

ATT-1950

EAN code	4007754179835
Net weight	1.379 kg