



EDL-250C/WS

Order No.: 0160110

PRODUCTINFOS

PA ceiling speaker,

with EN 54-24 certification.

- 100 V transmission technology
- Full range speaker with a very high efficiency and high maximum volume level
- Metal housing
- Fire protection cover
- Quick mounting facility
- 3 power taps via push terminals
- Ball-proof according to DIN 18032, Part 3

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

EDL-250C/WS

Transmission technology	100 V
Frequency range	70-19,000 Hz
Power rating (RMS)	6/3/1.5 W
SPL	98 dB (1 W/1 m) 81 dB (EN, 1 W/4 m)
Max. rated SPL	106 dB (1 m) 90 dB (EN, 4 m)
Radiation angle, horizontal	180° (500 Hz) 180° (1 kHz) 90° (2 kHz) 49° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 180° (1 kHz) 90° (2 kHz) 49° (4 kHz)
Mounting cutout	Ø 230 mm
Mounting depth	110 mm
Dimensions	Ø 252 mm x 110 mm
Outside diameter	Ø 252 mm
Width	Ø 252 mm
Height	Ø 252 mm
Depth	110 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	1.8 kg
Packing unit	1
Type of speaker	200
Packaging dimensions (W x H x L)	0.28 x 0.13 x 0.28 m
Gross weight	2.005 kg
Net weight	1.81 kg

EDL-250C/WS

EAN code	4007754233360
Net weight	1.81 kg