

**Safety Data Sheet dated 16/5/2019, version 5**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Mixture identification:

Trade name: SAFETY AIR

Trade code: A01141

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

PRODUCTS FOR AIR CONDITIONING SYSTEMS

Uses advised against:

do not use on humans and animals

1.3. Details of the supplier of the safety data sheet

Company:

STAC PLASTIC SPRAY S.R.L. Via E. De Nicola 9/11 10036 Settimo Torinese (To) Italia.

STAC PLASTIC SPRAY S.R.L. Tel. n.. +39 011 8977566 Fax n. +39 011 8977491

Competent person responsible for the safety data sheet:

Montini Vittorino stacplas@stacplastic.com

1.4. Emergency telephone number

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)

Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)

Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma)


Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)


---

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

 Warning, Skin Sens. 1, May cause an allergic skin reaction.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H317 May cause an allergic skin reaction.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

# Safety Data Sheet

## SAFETY AIR

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403 Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

alpha-Terpineol acetate - FEMA: May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

Product contents:

Non-ionic surfactants

< 5 %

The product also contains: Perfumes

Allergens:

Preservatives:

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

section 10.3




### SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	ethanol; ethyl alcohol	Index number: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 REACH No.: 01-2119457610-43-xxxx	 2.6/2 Flam. Liq. 2 H225
>= 30% - < 40%	propane	Index number: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	 2.2/1 Flam. Gas 1 H220  2.5 Press. Gas H280

## Safety Data Sheet

### SAFETY AIR

		REACH No.: 01-2119486944-21-0046	
>= 20% - < 25%	Hydrocarbons, C4; Petroleum gas	Index number: 649-113-00-2 CAS: 87741-01-3 EC: 289-339-5 REACH No.: 01-2119480480-41-xxxx	2.5 Press. Gas H280 2.2/1 Flam. Gas 1 H220 DECLK (CLP)*
>= 1% - < 3%	propan-2-ol; isopropyl alcohol; isopropanol	Index number: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH No.: 01-2119457558-25-xxxx	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336
>= 0.25% - < 0.5%	butanone; ethyl methyl ketone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0	2.6/2 Flam. Liq. 2 H225 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H336 EUH066
>= 0.1% - < 0.25%	alpha-Terpineol acetate - FEMA	CAS: 80-26-2	3.4.2/1 Skin Sens. 1 H317 4.1/C2 Aquatic Chronic 2 H411
193 ppm	1-methoxy-2-propanol; monopropylene glycol methyl ether	Index number: 603-064-00-3 CAS: 107-98-2 EC: 203-539-1 REACH No.: 01-2119457435-35-xxxx	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336
38 ppm	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	Index number: 613-167-00-5 CAS: 55965-84-9	3.2/1B Skin Corr. 1B H314 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317 4.1/A1 Aquatic Acute 1 H400 4.1/C1 Aquatic Chronic 1 H410 3.1/3/Oral Acute Tox. 3 H301 3.1/3/Dermal Acute Tox. 3 H311 3.1/3/Inhal Acute Tox. 3 H331

\*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3.

#### SECTION 4: First aid measures

A01141/5

Page n. 3 of 12

# Safety Data Sheet

## SAFETY AIR

### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

### 4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects due to the contained substances see chapter 11

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Follow the doctor's instructions.

---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Water.

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Do not inhale explosion and combustion gases.

### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Keep containers cool with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

Normal elements for fire fighting, such as a self-contained compressed air open-circuit respirator (EN 137), fire-retardant suit (EN469), flame-retardant gloves (EN 659) and fire boots (HO A29 or A30).

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

### 6.3. Methods and material for containment and cleaning up

For cleaning up:

Wash with plenty of water.

Wet clean or vacuum up solids.

# Safety Data Sheet

## SAFETY AIR

Clear spills immediately

Other information:

Don't use a brush or compressed air for cleaning surfaces or clothing.

### 6.4. Reference to other sections

See also section 8 and 13

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition

keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.

at work do not eat or drink.

do not smoke

avoid the accumulation of electrostatic charges.

Store at below 50 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

### 7.3. Specific end use(s)

None in particular

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

ethanol; ethyl alcohol - CAS: 64-17-5

ACGIH - STEL: 1000 ppm

propane - CAS: 74-98-6

ACGIH

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm

butanone; ethyl methyl ketone - CAS: 78-93-3

EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm

ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

EU - TWA(8h): 375 mg/m<sup>3</sup>, 100 ppm - STEL: 563 mg/m<sup>3</sup>, 150 ppm

ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm

### DNEL Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3

# Safety Data Sheet

## SAFETY AIR

Worker Professional: 1161 mg/kg/d - Consumer: 412 mg/kg/d - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Professional: 600 mg/l - Consumer: 106 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 31 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic effects

### PNEC Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3  
Target: Freshwater sediments - Value: 284.74 mg/kg  
Target: Marine water sediments - Value: 284.74 mg/kg  
Target: Soil (agricultural) - Value: 22.5 mg/kg  
Target: Fresh Water - Value: 55.8 mg/l  
Target: Marine water - Value: 55.8 mg/l

### 8.2. Exposure controls

#### Eye protection:

Basket eye glasses (standard EN 166)

#### Protection for skin:

Wear work clothes with long sleeves and protective footwear for professional use of category II (ref. Directive 89/686 / CEE and norm EN ISO 20344). Wash with soap and water after removing protective clothing.

#### Protection for hands:

Protect hands with category II work gloves (ref. Directive 89/686 / EEC and standard EN 374).  
Use PVC or nitrile rubber gloves.

#### Respiratory protection:

if the TLV thresholds are exceeded, use a mask with filter type A (against vapors of organic compounds) in accordance with EN 141.

#### Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

#### Environmental exposure controls:

None

#### Appropriate engineering controls:

None

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Spray can	--	--
Odour:	perfumed	--	--
Odour threshold:	Not Relevant	--	--
pH:	Not Relevant	--	--
Melting point / freezing point:	Not Relevant	--	--
Initial boiling point and boiling range:	Not Relevant	--	--
Flash point:	< 0 ° C	--	--
Evaporation rate:	Not Relevant	--	--
Solid/gas flammability:	Not Relevant	--	--
Upper/lower flammability or explosive limits:	Not Relevant	--	--
Vapour pressure:	5 bar +/- 1	--	--
Vapour density:	>2	--	--
Relative density:	0.620 kg/l +/-	--	--

## Safety Data Sheet

### SAFETY AIR

	0.05		
Solubility in water:	Not Relevant	--	--
Solubility in oil:	Not Relevant	--	--
Partition coefficient (n-octanol/water):	Not Relevant	--	--
Auto-ignition temperature:	>200°C	--	--
Decomposition temperature:	Not Relevant	--	--
Viscosity:	Not Relevant	--	--
Explosive properties:	section 10.3	--	--
Oxidizing properties:	Not Relevant	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	Not Relevant	--	--
Miscibility:	Not Relevant	--	--
Fat Solubility:	Not Relevant	--	--
Conductivity:	Not Relevant	--	--
Substance Groups relevant properties	Not Relevant	--	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

avoid contact with strong acids and bases and oxidizing agents.

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

may form explosive vapor / air mixtures in places not well ventilated

### 10.4. Conditions to avoid

keep away from heat, sources of ignition  
avoid the accumulation of electrostatic charges.

### 10.5. Incompatible materials

oxidizing agents  
acids, alkalis and alkaline metals

### 10.6. Hazardous decomposition products

the product is flammable, following combustion can lead to the formation of dangerous decomposition products  
by thermal decomposition can rid CO<sub>x</sub>  
during combustion it produces irritating gases

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological information of the product:

SAFETY AIR

#### a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

#### b) skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

#### c) serious eye damage/irritation

Not classified

# Safety Data Sheet

## SAFETY AIR

- Based on available data, the classification criteria are not met
- d) respiratory or skin sensitisation  
The product is classified: Skin Sens. 1 H317
- e) germ cell mutagenicity  
Not classified  
Based on available data, the classification criteria are not met
- f) carcinogenicity  
Not classified  
Based on available data, the classification criteria are not met
- g) reproductive toxicity  
Not classified  
Based on available data, the classification criteria are not met
- h) STOT-single exposure  
Not classified  
Based on available data, the classification criteria are not met
- i) STOT-repeated exposure  
Not classified  
Based on available data, the classification criteria are not met
- j) aspiration hazard  
Not classified  
Based on available data, the classification criteria are not met
- Toxicological information of the main substances found in the product:
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
- butanone; ethyl methyl ketone - CAS: 78-93-3
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
- ethanol; ethyl alcohol - CAS: 64-17-5  
LD50 (RABBIT) ORAL: 6300 MG/KG  
LD50 (RAT) ORAL SINGLE DOSE: 7060 MG/KG

---

## SECTION 12: Ecological information

- 12.1. Toxicity  
Adopt good working practices, so that the product is not released into the environment.
- SAFETY AIR  
Not classified for environmental hazards  
Based on available data, the classification criteria are not met
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- a) Aquatic acute toxicity:  
Endpoint: EL50 - Species: Daphnia > 100 mg/l - Duration h: 48  
Endpoint: EL50 - Species: Algae > 100 mg/l - Duration h: 72  
Endpoint: EL50 - Species: Fish > 100 mg/l - Duration h: 48
- butanone; ethyl methyl ketone - CAS: 78-93-3
- a) Aquatic acute toxicity:  
Endpoint: EL50 - Species: Daphnia = 308 mg/l - Duration h: 48  
Endpoint: EL50 - Species: Algae = 2029 mg/l - Duration h: 96  
Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96
- 12.2. Persistence and degradability  
None

# Safety Data Sheet

## SAFETY AIR

- butanone; ethyl methyl ketone - CAS: 78-93-3  
Biodegradability: Not persistent and Biodegradable
- 12.3. Bioaccumulative potential  
butanone; ethyl methyl ketone - CAS: 78-93-3  
Bioaccumulation: Not bioaccumulative
- 12.4. Mobility in soil  
butanone; ethyl methyl ketone - CAS: 78-93-3  
Mobility in soil: Mobile
- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None

---

### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.
- Additional disposal information:  
contaminated packaging should be sent for recovery or disposal in compliance with national regulations on waste management  
reuse if possible. Product residues are to be considered hazardous waste. disposal must be entrusted to authorised waste management, in compliance with national and, where appropriate, local.  
CER 160504

---

### SECTION 14: Transport information

- 14.1. UN number  
ADR-UN number: 1950  
IATA-Un number: 1950  
IMDG-Un number: 1950
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)  
ADR-Class: 2.5°F CAP. 2.2.2.1.6 UN1950  
IATA-Class: 2.1  
IMDG-Class: 2 Aerosols UN 1950
- 14.4. Packing group  
ADR- Packing group: N.A.  
IATA-Packing group: N.A.  
IMDG-Packing group: N.A.
- 14.5. Environmental hazards  
Marine pollutant: No
- 14.6. Special precautions for user  
ADR-Tunnel Restriction Code: N.A.  
IMDG-Page: 2102
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
No

---

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

# Safety Data Sheet

## SAFETY AIR

Regulation (EU) 2015/830  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Regulation (EU) n. 2016/918 (ATP 8 CLP)  
Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)  
Regulation (EC) nr 648/2004 (detergents).  
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1  
Product belongs to category: P3a

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

---

## SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.  
H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
H317 May cause an allergic skin reaction.  
H411 Toxic to aquatic life with long lasting effects.  
H226 Flammable liquid and vapour.  
H314 Causes severe skin burns and eye damage.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H301 Toxic if swallowed.  
H311 Toxic in contact with skin.  
H331 Toxic if inhaled.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B

## Safety Data Sheet

### SAFETY AIR

Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Paragraphs modified from the previous revision:

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Skin Sens. 1, H317	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.

## Safety Data Sheet

### SAFETY AIR

LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.