



ATT-250/WS

Order No.: 0170590

PRODUCTINFOS

Wall-mounted PA volume control

- Power rating: 50 W
- Attenuation in 10 steps, position 0 is OFF
- Audio transformer for 100 V transmission technology
- White plastic front panel and knob
- Flush mounting, surface mounting with matching housing ATT-200, available at option

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

During operation, there is a hazard of contact with a voltage of up to 100 V at the connection cables.

Installation must be carried out by skilled personnel only. Make sure that the power matching is correct. An overload will damage the power amplifier and the attenuator!

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

ATT-250/WS

Description	wall-mounted PA volume control
Frequency range	50-18,000 Hz
Power rating	50 W
Priority facility	no
Dimensions	85 x 85 x 71 mm
Mounting depth	42 mm
Weight	211 g
Surface-mounted housing	ATT-200

ATT-250/WS

EAN code	4007754090697
Net weight	0.211 kg