



ATS-16PS

Order No.: 0244670

PRODUCTINFOS

Intelligent PWM quick-charge station,

for simultaneously charging rech. batteries (NC, NiMH) of two devices from the ATS-16 series.

- Average charging time, depending on capacity and condition of the rechargeable batteries used: approx. 3-4 hours, e.g. for 1,300 mAh rech. batteries
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection
- Including plug-in power supply

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

ATS-16PS

Description	quick-charge station
Nominal value	2 devices
Type	PWM
Colour	black
Suitable for	ATS-16R, ATS-16T
Power supply	via encl. plug-in power supply
Admiss. ambient temp.	0-40 °C
Dimensions	85 x 70 x 106 mm
Weight	175 g
Packing unit	1
Packaging dimensions (W x H x L)	0.095 x 0.1 x 0.17 m
Gross weight	0.565 kg
Net weight	0.455 kg

ATS-16PS

EAN code	4007754191110
Net weight	0.455 kg