



## ATS-22T

Order No.: 0257120

### PRODUCTINFOS

#### 16-channel Digital Voice Transmission System, 863-865 MHz

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmission
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

#### 16-channel miniature transmitter,

for microphone operation and audio line signals, with intercom function.

- Supplied with headset
- Activation switch for intercom function with the receiver ATS-22R
- Audio line input via 3.5 mm jack at the headset
- LCD for indicating channel and battery status
- Mute button
- Transmitting power:  $\leq 10$  mW (EIRP), operating range: approx. 70 m
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)

- Micro USB charging connection for ATS-12CB, ATS-35CB or USB charger, available at option
- Dimensions: 40 x 80 x 12 mm
- Weight: 37 g

### Licence-free in the EU.

### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Konsul-Smidt-Str. 68  
28217 Bremen  
Germany  
info@monacor.com

### Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

## TECHNICAL SPECIFICATIONS

### ATS-22T

#### General information

Description	16-channel digital miniature transmitter
Carrier frequency range	863-865 MHz
Channels	1
Operating time	> 12 h
Admiss. ambient temp.	0-40 °C

#### Specifications transmitter

Transmitting power	≤ 10 mW
Operating range	70 m
Power supply transmitter	integrated rech. lithium batt. (3.7 V/600 mAh)
Width transmitter	40 mm
Height transmitter	80 mm

**ATS-22T**

Depth transmitter	12 mm
Weight transmitter	37 g
Connections transmitter	3.5 mm jack (microphone/line in), micro USB charging port

**ATS-22T**

EAN code	4007754246247
Net weight	0.055 kg