



AVIO-A-2IN-EB



Order No.: 1001504

PRODUCTINFOS

Reliable audio integration for fixed installation projects.

The AVIO-A-2IN-EB provides a professional solution for integrating analogue audio sources in Dante[®]-based networks. With Euroblock connections and PoE supply the adapter is designed specifically for the use in fixed installations - perfect for AV system houses, specialist electrical companies and planning offices.

Dante[®] AVIO analogue input adapter (2-channel)

- Euroblock inputs for simple and secure hardwiring
- Dante[®] network connection (RJ45), compatible with Dante[®] and AES67
- PoE power supply (802.3af class 1), no separate power supply unit required
- Adjustable input level: +4/0 dBu/0/-10 dBV (via Dante[®] controller)
- Frequency range 20-20,000 Hz
- Impedance 20 k Ω (bal.), 10 k Ω (unbal.)
- Sample rate 44.1/48/96 kHz, 16/24/32 Bit
- Supports Dante[®] Domain Manager for IT-compliant management and security
- Robust housing, suitable for wall or rack mounting

Typical application scenarios:

- AV installations in conference rooms, lecture theatres and houses of worship
- Integration of analogue players, microphone receivers or DSPs
- Expansion of existing Dante® networks with analogue sources

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

Manufacturer information:

Audinate Ltd.
Future Business Centre
Kings Hedges Rd
Cambridge CB4 2HY
United Kingdom
info@audinate.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

AVIO-A-2IN-EB

Description	Dante® AVIO analogue input adapter
Type	2-channel
Colour	black
Power supply	PoE
Admiss. ambient temp.	-10 °C to +45 °C
Weight	145 g
Connections	1 x RJ45, 1 x 6-pole Euroblock, 3.5 mm
Packing unit	1
Packaging dimensions (W x H x L)	0.19 x 0.0925 x 0.045 m

AVIO-A-2IN-EB

Gross weight 0.206 kg

Net weight 0.145 kg

AVIO-A-2IN-EB

EAN code 9353345000091

Net weight 0.145 kg

AVIO-A-2IN-EB

Sampling rates 44.1/48/96 kHz

Resolution 16/24/32 bit