

# T distributor - SAC-5PT-F/F-M VP - 1424712

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



T distributor, CANopen<sup>®</sup>, DeviceNet<sup>™</sup>, 5-position, unshielded, Socket straight M12, A-coded, on Socket straight M12, A-coded and Plug straight M12, A-coded, Parallel distributor

#### Your advantages

Safe use in the field, thanks to a high degree of protection



## **Key Commercial Data**

Packing unit	1 pc
GTIN	4 055626 376752
GTIN	4055626376752

#### Technical data

#### Ambient conditions

Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)
Degree of protection	IP65

#### General

Rated current at 40°C	4 A
Rated voltage	60 V DC
	48 V AC
Number of positions	5
Color handle area	black
Coding	A-coded
Standards/regulations	M12 connector IEC 61076-2-101
Signal type/category	CANopen <sup>®</sup>
	DeviceNet™
Status display	No
Overvoltage category	II
Degree of pollution	3

04/08/2019 Page 1 / 3



# T distributor - SAC-5PT-F/F-M VP - 1424712

## Technical data

## General

Insertion/withdrawal cycles	≥ 100
Torque	0.4 Nm (M12 connector)

#### Material

Flammability rating according to UL 94	V0
Contact material	CuZn (pin) / CuSn (socket)
Contact surface material	Ni/Au
Contact carrier material	PBT
Material of grip body	PBT
Material, knurls	Zinc die-cast, nickel-plated
Sealing material	NBR

#### Characteristics head 2

Color	black
00101	black

## Standards and Regulations

Standard designation	M12 connector
Standards/regulations	IEC 61076-2-101
Flammability rating according to UL 94	V0

## **Environmental Product Compliance**

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## **Drawings**

Schematic diagram



Schematic diagram




Pin assignment M12 male connector, 5-pos., A-coded, male side


Pin assignment M12 socket, 5-pos., A-coded, socket side view



# T distributor - SAC-5PT-F/F-M VP - 1424712

#### Dimensional drawing





M12 T distributor

Contact assignment of the M12 plug and the M12 socket

## Approvals

Approvals

Approvals

EAC

Ex Approvals

#### Approval details



EAC-Zulassung

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com