

172x150x51mm (6.77x5.91x2.00in) - 5 blade



Bearing System— 2 Ball Bearing,
 Life Expectancy--- Ball 70000hrs@ 25°C
 Frame-----Aluminu
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0
 Lead Wire----- UL 1007, AWG 24, 220±10mm, Red(+), Black(-)
 Protection----- Locked rotor protection
 IP Grade ----- Optional



Dim: 450x380x360mm
 N.W.: 15.0 kgs
 G.W.: 18.0 kgs
 Q'TY: 20 pcs

FUNCTIONS	PART NUMBER	RATED (VDC)	LABEL CURRENT	ACTUAL CURRENT	POWER (WATTS)	SPEED (RPM)	AIRFLOW (CFM)(m³/min)	PRESSURE (mmAq)(In H²O)	NOISE (dBA)	WEIGHT (Q'TY/CTN)
1b:AS 2a:FG 2b:RD 2c:RDb 2d:LD 1a:IR 6:CL 3c:PPWM 3a:VPWM 5a:TPWM 5b:RPWM 3b:IPWM 7a:CS	P1751H12BALBxy-5	12	2.170	1.512	18.14	3500	251.97 7.13	17.31 0.68	57.70	750g
	P1751M12BALBxy-5	(08~14)	1.560	0.850	10.20	3000	215.97 6.12	12.72 0.50	53.68	(20pcs)
	P1751L12BALBxy-5		0.670	0.540	6.48	2500	179.98 5.10	8.83 0.35	48.93	
	P1751Z24BALBxy-5		2.131	1.800	43.20	5200	374.35 10.60	38.21 1.50	68.01	
	P1751Y24BALBxy-5	24	2.340	1.200	28.80	4500	323.96 9.17	28.61 1.13	64.24	750g
	P1751X24BALBxy-5	(15~27)	1.430	0.834	20.02	4000	287.96 8.15	22.61 0.89	61.18	(20pcs)
	P1751H24BALBxy-5		0.980	0.600	14.40	3500	251.97 7.13	17.31 0.68	57.70	
	P1751M24BALBxy-5		0.630	0.420	10.08	3000	215.97 6.12	12.72 0.50	53.68	
	P1751L24BALBxy-5		0.360	0.290	6.96	2500	179.98 5.10	8.83 0.35	48.93	
	P1751Z48BALBxy-5		1.159	0.875	42.00	5200	374.35 10.60	38.21 1.50	68.01	
	P1751Y48BALBxy-5	48	1.100	0.567	27.22	4500	323.96 9.17	28.61 1.13	64.24	750g
	P1751X48BALBxy-5	(36~57)	0.710	0.410	19.68	4000	287.96 8.15	22.61 0.89	61.18	(20pcs)
	P1751H48BALBxy-5		0.500	0.298	14.30	3500	251.97 7.13	17.31 0.68	57.70	
	P1751M48BALBxy-5		0.390	0.230	11.04	3000	215.97 6.12	12.72 0.50	53.68	
	P1751L48BALBxy-5		0.200	0.164	7.87	2500	179.98 5.10	8.83 0.35	48.93	

