

## 25x25x10mm (0.98x0.98x0.39in) - 5 blade



Bearing System— 2 Ball Bearing,  
 Life Expectancy--- Ball 70000hrs@ 25°C  
 Frame----- Thermoplastic PBT+30% GF, UL94-V0  
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0  
 Lead Wire----- UL 1061, AWG 30, 240±10mm, Red(+), Black(-)  
 Protection----- Locked rotor protection  
 IP Grade ----- Optional



Dim: 494x423x155 mm  
 N.W.: 8.2 kgs  
 G.W.: 10.7 kgs  
 Q'TY: 1080 pcs

FUNCTIONS	PART NUMBER	RATED	LABEL	ACTUAL	POWER	SPEED	AIRFLOW	PRESSURE	NOISE	WEIGHT
		(VDC)	CURRENT	CURRENT	(WATTS)	(RPM)	(CFM)(m³/min)	(mmAq)(In H²O)	(dBA)	(Q'TY/CTN)
1b:AS 2a:FG	D2510H05BPLBxy-5	05	0.260	0.220	1.10	13000	2.60 0.07	6.67 0.26	30.54	7.6g (1080pcs)
	D2510M05BPLBxy-5	(04~06)	0.190	0.190	0.95	10000	2.02 0.06	4.05 0.16	24.21	
	D2510L05BPLBxy-5		0.140	0.140	0.70	7000	1.39 0.04	1.98 0.08	18.14	
	D2510X12BPLBxy-5	12 (07~14)	0.136	0.130	1.56	15000	2.92 0.08	8.00 0.32	34.19	7.6g (1080pcs)
	D2510H12BPLBxy-5		0.090	0.090	1.08	13000	2.60 0.07	6.67 0.26	30.54	
	D2510M12BPLBxy-5		0.070	0.070	0.84	10000	2.02 0.06	4.05 0.16	24.21	
	D2510L12BPLBxy-5		0.060	0.060	0.72	7000	1.39 0.04	1.98 0.08	18.14	

Remark: 1. Part no. suffix: "xy"=Function detail or "x"=Function number, "y"=customer ID  
 2. C series - STANDARD series: use a 2 coil complementary type drive offering low cost and limited functions.

