Tenda

Cod. 486622392

F9 600Mbps Who le-H ome Coverage Wi-Fir outer

F9 is a 6 00Mbps High Speed and who le-home coverage Wi-Fir outer. The wireless transmission r ate of F9 is upt o 6 00Mbps. Compared to 45 0Mbps and 3 00Mbps products, it's transmission is more efficient and smooth, support more equipments connection at the same time. Its built-in signal amplifiers, Beamforming technology, and four external ant ennas offer you lag-free gaming and unint errupted video streaming experience. F9 also provides the Smart WiFi Schedule function, which automatically turns on/off WiFi to reduce power consumption and bring smart internet connectivity to your family.





600M ps for super f ast experience

33% faster than 45 0Mbps r outer, F9 allo ws y ou to enjo y much f aster internet experience



Powerful co verage & w all penetr ation

Four ext ernal 6 dBi ant ennas and Beamf orming+t echno logy ensur e powerful coverage and wall penetr ation for small and medium apartments



Smart app f or con venient r emot e management

Tenda app allo ws users to remotely manage the devices connected to it and black list the unauthorized users with a single tap

Featur es

- Transfer rate up t o 6 00Mbps
- Four ext ernal 6 dBi ant ennas
- Management wit h Tenda App

- Support WiFiT urn on/off
- Support wir eless signal r epeater and WISP

Specifications

Hardware Specifications	
Wired Communications Standards	IEEE b/g/n,IEEE 802.3/3u
Interface	1*10/100Mbps WAN port, 3* 10/100Mbps LAN ports
Antennas	External 6 dBi omnidirectional antenna × 4
Button	1*WPS/RST,1*WIFI
Power Supply	Input:100-240V-50/60Hz,0.3A Output:DC 9V==0.6A
Dimensions	171.3mm*171.3mm*36.4mm
LED Indicator	Systemx1; WiFi x1; LANx3; WAN x1; WPS x1
Wireless Features	
Wireless Communications Standards	IEEE802.11b,IEEE 802.11g, IEEE 802.11n
Data Rate	802.11b : 11 Mbps 802.11g : 54 Mbps 802.11n : 450Mbps 802.11n (256QAM): 600Mbps
Frequency	2.4 GHz
Transmit Power	802.11b-1M: 21.5 dBm ± 1.5 dBm 802.11g-54M: 17.5 dBm ± 1.5 dBm 802.11n-MCS7: 17 dBm ± 1.5 dBm 802.11n-VHT: 15 dBm ± 1.5 dBm
Wireless Security	Encryption Mode:WPA2-PSK WPA Algorithm:AES, TKIP, TKIP&AES
Software Features	
Standard Version	RFC768 UDP RFC791 IP RFC792 ICMP RFC793 TCP Channel Bandwidth: 20MHz, 20/40MHz
DHCP Server	Support
Working Mode	Router, WISP, Universal repeater, AP
System Tool	Internet time,Backup/Recovery,Upgrade; Reset to Factory Default; Login Password; System Log; Reboot
Special Features	Smart WiFi schedule Smart power saving Smart LED schedule Tenda Cloud Tenda APP

Specifications

Temperature	Operating Temperature:0°C~40°C
	Storage Temperature:-40~70°C
Humidity	Operating Humidity:10%~90%, non-condensing
	Storage Humidity:5%~90%, non-condensing
Default Login Domain Name	tendawifi.com
	1 * 600Mps Wireless N Router
	1 * Quick Installation Guide
Packing List	1 * Power Adapter
	1 * Ethernet Cable

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int' l E-City, #1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

Tel:+86-755-2765 7098 Fax:+86-755-2765 7178 PC:518055

Specifica?ons are subject to change without no?ce.Copyright ©2017 SHENZHEN TENDA TECHNOLOGY CO., LTD. All rights reserved. Tenda is the trademark of SHENZHEN TENDA TECHNOLOGY CO., LTD. All other brand names men?oned herein are the trademark or registered trademarks of their respec?ve holders.