


Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	7AH	
Dimensions	Length	151±2mm (5.94 inches)
	Width	65±1mm (2.54 inches)
	Container Height	93.5±1mm (3.68 inches)
	Total Height (with Terminal)	99±1mm (3.90 inches)
Approx Weight	Approx 1.9kg	
Terminal	T1 Faston 4.8 mm	
Container Material	ABS	
Rated Capacity	6.50 AH/0.325A	(20hr ,1.80V/cell,25 °C/77 °F)
	6.05 AH/0.605A	(10hr,1.80V/cell,25 °C/77 °F)
	5.55 AH/1.11A	(5hr,1.75V/cell,25 °C/77 °F)
	4.98AH/1.66A	(3hr,1.75V/cell,25 °C/77 °F)
	4.08 AH/4.08A	(1hr,1.60V/cell,25 °C/77 °F)
Max. Discharge Current	97.5A (5s)	
Internal Resistance	Approx 30m Ω	
Operating Temp.Range	Discharge : -15 ~50°C (5 ~122°F)	
	Charge : 0 ~40°C (32 ~104°F)	
	Storage : -15 ~40°C (5 ~104°F)	
Nominal Operating Temp. Range	25 ±3°C (77 ±5°F)	
Cycle Use	Initial Charging Current less than 1.95A.Voltage	
	14.4V~15.0V at 25°C (77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C (77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	MKC series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply(UPS)
- ◆ Electric Power System(EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77 °F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	12.4	9.51	7.87	6.81	5.26	3.88	3.27	1.93	1.51	1.23	1.00	0.870	0.702	0.586	0.322
1.80V/cell	16.6	12.1	9.51	8.05	6.21	4.51	3.66	2.11	1.63	1.31	1.08	0.933	0.744	0.605	0.325
1.75V/cell	18.7	13.3	10.39	8.66	6.45	4.68	3.83	2.19	1.66	1.34	1.11	0.959	0.757	0.621	0.328
1.70V/cell	20.6	14.5	11.1	9.10	6.71	4.87	3.95	2.24	1.70	1.38	1.13	0.979	0.768	0.633	0.334
1.65V/cell	22.7	15.7	11.8	9.67	7.08	4.99	4.04	2.28	1.78	1.43	1.16	1.00	0.780	0.646	0.339
1.60V/cell	25.1	17.0	12.6	10.3	7.48	5.20	4.08	2.37	1.83	1.47	1.20	1.02	0.788	0.653	0.341




Constant Power Discharge (Watts) at 25 °C (77 °F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	22.6	17.6	14.7	12.8	10.0	7.45	6.31	3.75	2.95	2.40	1.97	1.71	1.39	1.16	0.637
1.80V/cell	30.1	22.2	17.5	14.9	11.7	8.60	7.02	4.07	3.15	2.55	2.10	1.83	1.47	1.19	0.643
1.75V/cell	33.2	24.0	18.9	15.9	12.0	8.84	7.32	4.20	3.20	2.60	2.15	1.87	1.49	1.23	0.648
1.70V/cell	35.5	25.5	19.9	16.6	12.4	9.16	7.52	4.30	3.28	2.67	2.20	1.91	1.51	1.25	0.660
1.65V/cell	38.6	27.3	21.0	17.5	13.0	9.31	7.64	4.34	3.41	2.75	2.25	1.94	1.53	1.27	0.668
1.60V/cell	41.6	29.0	22.1	18.5	13.6	9.65	7.67	4.50	3.50	2.82	2.32	1.98	1.54	1.28	0.671


Dimensions

T1 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



A No supplementary charging required (Carry out supplementary charging before use if 100% capacity is required.)

Supplementary charging is required before use. Optional charging ways as below:
 1. Charged for a above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for a above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
 3. Charged for 8 ~10 hours at limited current 0.05 CA.

B Supplementary charging may often fail to recover the capacity. The battery should never be left standing until this is reached.