


UT213 SERIES 400A Digital Clamp Meters

UT213A / UT213B / UT213C



Intertek

UNI-T®



■ UT213A



■ UT213B



■ UT213C
Cod. 530134369

V.F.C. NCV REL AUTO RANGE

TRUE RMS DATA HOLD

SPECIFICATIONS

Specifications	Range	530134369		
Model		UT213A	UT213B	UT213C
AC Current (A)	4A/40A/400A	±(1.8%+9)	±(1.8%+9)	±(2.5%+5)
DC Current (A)	40A/400A			±(2.0%+3)
AC Voltage (V)	4V/40V/400V/600V	±(1.2%+5)	±(1.2%+5)	±(1.2%+5)
DC Voltage (V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance (Ω)	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1.0%+2)	±(1.0%+2)	±(1.0%+2)
Capacitance (F)	50nF/500nF/5μF/50μF/100μF	±(4.0%+5)		
	40nF/400nF/4μF/40μF/400μF/4mF/40mF		±(4.0%+5)	±(4.0%+5)
Frequency (Hz)	10Hz-1MHz	±(0.1%+4)	±(0.1%+4)	±(0.1%+4)
Temperature (°C)	-40 °C ~1000 °C		±(1.0%+3)	±(1.0%+3)
Temperature (°F)	-40 °F ~1832 °F		±(1.0%+6)	±(1.0%+6)
Features				
Display Count		4000	4000	4000
Auto Range		✓	✓	✓
Jaw Capacity		30mm	30mm	30mm
True RMS		✓	✓	✓
Diode		Around 1.5V	Around 3.0V	Around 3.0V
NCV		✓	✓	✓
Data Hold		✓	✓	✓
Relative Mode		✓	✓	✓
MAX/MIN			✓	✓
LCD Backlight		✓	✓	✓
Flashlight		✓	✓	✓
Auto Power Off		✓	✓	✓
Continuity Buzzer		✓	✓	✓
Low Battery Indication	≤3.6V	✓	✓	✓
Input Protection		✓	✓	✓
Input Impedance for DCV	≥10MΩ	✓	✓	✓

GENERAL CHARACTERISTICS

Power	AAA 1.5V x 3
LCD Size	38mm x 24 mm
Product Color	Red and Grey
Product Net Weight	UT213A/B - 280g UT213C - 231.7g
Product Size	220mm x 75mm x 40mm
Standard Accessories	UT213A-Batteries, Test Lead UT213B/C-Batteries, Test Lead, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, Carrying Bag, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	485mm x 320mm x 385mm (0.060 CBM Per Standard Carton)
Standard Carton Gross Weight	UT213A/B - 23 Kg UT213C - 20 Kg

Uni-Trend Your Testing Specialist !