



Sample photo

Order symbol: PC 95/60 HG
Product nbr: 6011331
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074054630
El. number:
Finland: 3421364
Electric No. Denmark: 8212027721
Electric No. Sweden: 6011331

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:		
mm:	100	100	60	MIN 8 DIN-15 Mounting rail	
inch:	3.9	3.9	2.4	B-3 DIN-35 Mounting rail	
				FP 22046 Wall fastening lug (4 pcs)	
Materials:				Rating:	
Material:	Polycarbonate			Ingress Protection (EN 60529): IP66/IP67	
Base colour:	RAL 7035 -light grey			Impact Resistance (EN 62262): IK08	
Cover screws material:	Polyamide			Electrical insulation: Totally insulated	
Cover colour:	RAL 7035 -light grey			Halogen free (DIN/VDE 0472, Part 815): 1	
Cover screws colour:	Grey			UV resistance: UL 508	
Gasket material:	Polyurethane			Flammability Rating: UL 746C 5"	
				Glow Wire Test (IEC 695-2-1) °C: 960	
				NEMA Class: NEMA 1, 4, 4X, 6, 12, 13	
Temperatures:				Certificates:	
Temperature °C (short term):	-40 ... 120 °C			SGS Fimko	
Temperature °C (continuous):	-40 ... 80 °C			Gost R	
Temperature °F (short term):	-40 ... 250 °F				
Temperature °F (continuous):	-40 ... 175 °F				
Accessories:					
MIV 95	Mounting plate (Galvanized steel)				

