

## MNX PC 175/75 HT



Sample photo

**Order symbol:** PC 175/75 HT  
**Product nbr:** 6011920  
**Description:** Enclosure, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074024435  
**El. number:**  
Finland: 3422254  
Electric No. Denmark: 8212022690  
Electric No. Italy: 7352113  
Electric No. Sweden: 2535664

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

| Dimensions:                  |                                   |     | Accessories:                             |                            |                      |
|------------------------------|-----------------------------------|-----|------------------------------------------|----------------------------|----------------------|
| mm:                          | 180                               | 180 | 75                                       | MIN 15                     | DIN-15 Mounting rail |
| inch:                        | 7.1                               | 7.1 | 3.0                                      | MIV 15                     | DIN-35 Mounting rail |
| Materials:                   |                                   |     | FP A 175/180                             | Front plate (Aluminium)    |                      |
| Material:                    | Polycarbonate                     |     | HFP 180                                  | Front plate hinge series   |                      |
| Base colour:                 | RAL 7035 -light grey              |     | FP 22046                                 | Wall fastening lug (4 pcs) |                      |
| Cover screws material:       | Polyamide                         |     | Rating:                                  |                            |                      |
| Cover colour:                | Smoked grey                       |     | Ingress Protection (EN 60529): IP66/IP67 |                            |                      |
| Cover screws colour:         | Black                             |     | Impact Resistance (EN 62262): IK08       |                            |                      |
| Gasket material:             | TPE                               |     | Electrical insulation: Totally insulated |                            |                      |
| Temperatures:                |                                   |     | Halogen free (DIN/VDE 0472, Part 815): 1 |                            |                      |
| Temperature °C (short term): | -40 ... 120 °C                    |     | UV resistance: UL 508                    |                            |                      |
| Temperature °C (continuous): | -40 ... 80 °C                     |     | Flammability Rating: UL 746C 5"          |                            |                      |
| Temperature °F (short term): | -40 ... 250 °F                    |     | Glow Wire Test (IEC 695-2-1) °C: 960     |                            |                      |
| Temperature °F (continuous): | -40 ... 175 °F                    |     | NEMA Class: NEMA 1, 4, 4X, 6, 12, 13     |                            |                      |
| Accessories:                 |                                   |     | Certificates:                            |                            |                      |
| MIV 175                      | Mounting plate (Galvanized steel) |     | SGS Fimko                                |                            |                      |
|                              |                                   |     | Gost R                                   |                            |                      |

