

MNX PC 150/50 LT



Sample photo

Order symbol: PC 150/50 LT
Product nbr: 6012914
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN:	6418074022387
El. number:	
Finland:	3420453
Electric No.	8212022438
Denmark:	
Electric No. Italy:	7352075
Electric No. Sweden:	2535642

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:		
mm:	180	130	50	MIN 10	DIN-15 Mounting rail
inch:	7.1	5.1	2.0	MIN 15	DIN-15 Mounting rail
				MIV 10	DIN-35 Mounting rail
				MIV 15	DIN-35 Mounting rail
Materials:					
Material:	Polycarbonate		FP A 150/180		Front plate (Aluminium)
Base colour:	RAL 7035 -light grey		HFP 180		Front plate hinge series
Cover screws material:	Polyamide		FP 22046		Wall fastening lug (4 pcs)
Cover colour:	Smoked grey				
Cover screws colour:	Black				
Gasket material:	TPE				
Temperatures:			Rating:		
Temperature °C (short term):	-40 ... 120 °C		Ingress Protection (EN 60529): IP66/IP67		
Temperature °C (continuous):	-40 ... 80 °C		Impact Resistance (EN 62262): IK08		
Temperature °F (short term):	-40 ... 250 °F		Electrical insulation: Totally insulated		
Temperature °F (continuous):	-40 ... 175 °F		Halogen free (DIN/VDE 0472, Part 815): 1		
			UV resistance: UL 508		
			Flammability Rating: UL 746C 5"		
			Glow Wire Test (IEC 695-2-1) °C: 960		
			NEMA Class: NEMA 1, 4, 4X, 6		
Accessories:			Certificates:		
MIV 150	Mounting plate (Galvanized steel)		SGS Fimko		
			Gost R		

