



Sample photo

Order symbol: PC 150/85 XHG
Product nbr: 6013333
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074061201
El. number:
Finland: 3435602
Electric No. Denmark: 8212027967
Electric No. Sweden: 6013333

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:		
mm:	180	130	85	MIN 10	DIN-15 Mounting rail
inch:	7.1	5.1	3.3	MIN 15	DIN-15 Mounting rail
Materials:			MIV 10	DIN-35 Mounting rail	
Material:	Polycarbonate		MIV 15	DIN-35 Mounting rail	
Base colour:	RAL 7035 -light grey		FP A 150/180	Front plate (Aluminium)	
Cover screws material:	Polyamide		HFP 180	Front plate hinge series	
Cover colour:	RAL 7035 -light grey		FP 22046	Wall fastening lug (4 pcs)	
Cover screws colour:	Grey				
Gasket material:	Polyurethane				
Temperatures:			Rating:		
Temperature °C (short term):	-40 ... 120 °C		Ingress Protection (EN 60529): IP66/IP67		
Temperature °C (continuous):	-40 ... 80 °C		Impact Resistance (EN 62262): IK08		
Temperature °F (short term):	-40 ... 250 °F		Electrical insulation: Totally insulated		
Temperature °F (continuous):	-40 ... 175 °F		Halogen free (DIN/VDE 0472, Part 815): 1		
Accessories:			UV resistance: UL 508		
MIV 150	Mounting plate (Galvanized steel)		Flammability Rating: UL 746C 5"		
			Glow Wire Test (IEC 695-2-1) °C: 960		
			NEMA Class: NEMA 1, 4, 4X, 6		

