



Sample photo

**Order symbol:** PCT 203615  
**Product nbr:** 7022791  
**Description:** Enclosure, PC  
**Remarks:** Clear transparent cover

**EAN:** 6418074058713  
**El. number:**  
**Finland:** 3435422  
**Electric No. Denmark:** 8212003033  
**Electric No. Sweden:** 7022791

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

| Dimensions:                  |                      |     | Rating:                                  |
|------------------------------|----------------------|-----|------------------------------------------|
| mm:                          | 360                  | 200 | Ingress Protection (EN 60529): IP66/IP67 |
| inch:                        | 14.2                 | 7.9 | Impact Resistance (EN 62262): IK07/IK08  |
|                              |                      |     | Electrical insulation: Totally insulated |
| Materials:                   |                      |     | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Material:                    | Polycarbonate        |     | UV resistance: UL 508                    |
| Base colour:                 | RAL 7035 -light grey |     | Flammability Rating: UL 746C 5"          |
| Cover screws material:       | Stainless steel      |     | Glow Wire Test (IEC 695-2-1) °C: 960     |
| Cover colour:                | Clear transparent    |     | NEMA Class: NEMA 1, 4, 4X, 12, 13        |
| Gasket material:             | Polyurethane         |     |                                          |
| Temperatures:                |                      |     | Certificates:                            |
| Temperature °C (short term): | -40 ... 120 °C       |     | SGS Fimko                                |
| Temperature °C (continuous): | -40 ... 80 °C        |     | Gost R                                   |
| Temperature °F (short term): | -40 ... 250 °F       |     |                                          |
| Temperature °F (continuous): | -40 ... 175 °F       |     |                                          |

EURONORD PC/ABS 360x200x151

