

80x80x38mm (3.15x3.15x1.5in) - 7 blade



Bearing System— 2 Ball Bearing
 Life Expectancy— Ball 70000hrs@ 25°C
 Frame----- Thermoplastic PBT+30% GF, UL94-V0
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0
 Lead Wire----- UL 1007, AWG 24, 260±10mm, Red(+), Black(-)
 Protection----- Locked rotor protection
 IP Grade ----- Optional



Dim: 493x339x218mm
 N.W.: 12.0 kgs
 G.W.: 13.5 kgs
 Q'TY: 60 pcs

FUNCTIONS	PART NUMBER	RATED (VDC)	LABEL CURRENT	ACTUAL CURRENT	POWER (WATTS)	SPEED (RPM)	AIRFLOW (CFM)(m³/min)	PRESSURE (mmAq)(In H²O)	NOISE (dBA)	WEIGHT (Q'TY/CTN)
1b:AS 2a:FG 2b:RD 2c:RDb 2d:LD 1a:IR 6:CL 3c:PPWM 3a:VPWM 5a:TPWM 5b:RPWM 3b:IPWM 7a:CS	K8038X12BPLBxy-7	12 (08~14)	2.150	1.350	16.20	8000	112.53	3.19	35.57	200g (60pcs)
	K8038H12BPLBxy-7		1.430	0.900	10.80	7000	98.47	2.79	27.23	
	K8038M12BPLBxy-7		0.720	0.500	6.00	5500	77.37	2.19	16.81	
	K8038L12BPLBxy-7		0.330	0.250	3.00	4000	56.27	1.59	8.89	
	K8038Y24BPLBxy-7	24 (15~27)	1.760	1.200	28.80	10000	140.67	3.98	55.58	200g (60pcs)
	K8038X24BPLBxy-7		1.200	0.900	21.60	8500	119.57	3.39	40.15	
	K8038H24BPLBxy-7		0.650	0.400	9.60	7000	98.47	2.79	27.23	
	K8038M24BPLBxy-7		0.340	0.300	7.20	5500	77.37	2.19	16.81	
	K8038L24BPLBxy-7	48 (36~57)	0.170	0.160	3.84	4000	56.27	1.59	8.89	200g (60pcs)
	K8038Y48BPLBxy-7		0.850	0.600	28.80	10000	140.67	3.98	55.58	
	K8038X48BPLBxy-7		0.530	0.490	23.52	8500	119.57	3.39	40.15	
	K8038H48BPLBxy-7		0.330	0.250	12.00	7000	98.47	2.79	27.23	
	K8038M48BPLBxy-7		0.200	0.165	7.92	5500	77.37	2.19	16.81	
	K8038L48BPLBxy-7		0.100	0.090	4.32	4000	56.27	1.59	8.89	

