

ARCA 403015



Sample photo

Order symbol: ARCA 403015
Product nbr: 8120006
Description: Cabinet, PC
Remarks: 2-point locking

EAN: 6418074079176
El. number:
Finland: 3423051
Electric No. 8212091045
Denmark:
Electric No. Sweden: 2500112

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height
mm:	400	300	150
inch:	15.7	11.8	5.9

Materials:

Material: Polycarbonate
Base colour: RAL 7035 -light grey
Cover colour: RAL 7035 -light grey
Gasket material: Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 120 °C
Temperature °C (continuous): -40 ... 80 °C
Temperature °F (short term): -40 ... 250 °F
Temperature °F (continuous): -40 ... 175 °F

Accessories:

MPS ARCA 4030 Mounting plate (350x250x2 mm)

Accessories:

MPP ARCA 4030 Mounting plate perforated (350x250x2 mm - 26x11 mm)
MPMP ARCA 4030 Mounting plate multiperforated (350x250x2 mm - □3.6 mm)
MPX ARCA 4030 Mounting plate (350x250 mm)
DRS ARCA 403015 DIN rail frame set
IDS ARCA 4030 Inner door set
PMK ARCA 30 Pole mounting kit
RCS ARCA 4030 Rain canopy set
SBK ARCA 30 Support bar kit
SBK ARCA 40 Support bar kit
DSP ARCA VLS Door stopper ARCA, vertical, left, small
DSP ARCA VRS Door stopper ARCA, vertical, right, small

Rating:

Ingress Protection (EN 60529): IP66
Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C: 960

Certificates:

SGS Fimko
Gost R

