

ARCA 504021



Sample photo

Order symbol: ARCA 504021
Product nbr: 8120011
Description: Cabinet, PC
Remarks: 2-point locking

EAN: 6418074079220
El. number:
Finland: 3423099
Electric No. 8212091090
Denmark:
Electric No. Sweden: 2500116

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height
mm:	500	400	210
inch:	19.7	15.7	8.3

Materials:

Material: Polycarbonate
Base colour: RAL 7035 -light grey
Cover colour: RAL 7035 -light grey
Gasket material: Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 120 °C
Temperature °C (continuous): -40 ... 80 °C
Temperature °F (short term): -40 ... 250 °F
Temperature °F (continuous): -40 ... 175 °F

Accessories:

MPS ARCA 5040 Mounting plate (450x350x2 mm)

Accessories:

MPP ARCA 5040 Mounting plate perforated (450x350x2 mm - 26x11 mm)
MPMP ARCA 5040 Mounting plate multiperforated (450x350x2 mm - □3.6 mm)
MPX ARCA 5040 Mounting plate (450x350 mm)
DRS ARCA 504015 DIN rail frame set
DRS ARCA 504021 DIN rail frame set
IDS ARCA 5040 Inner door set
PMK ARCA 40 Pole mounting kit
RCS ARCA 5040 Rain canopy set
SBK ARCA 40 Support bar kit
SBK ARCA 50 Support bar kit
DSP ARCA VLS Door stopper ARCA, vertical, left, small
DSP ARCA VRS Door stopper ARCA, vertical, right, small

Rating:

Ingress Protection (EN 60529): IP66
Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C: 960

Certificates:

SGS Fimko
Gost R

