

ARCA 304015



Sample photo

Order symbol: ARCA 304015
Product nbr: 8120022
Description: Cabinet, PC
Remarks: 2-point locking

EAN: 6418074079336
El. number:
Finland: 3423119
Electric No. Denmark: 8212091207
Electric No. Sweden: 2500111

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height
mm:	300	400	150
inch:	11.8	15.7	5.9

Materials:

Material: Polycarbonate
Base colour: RAL 7035 -light grey
Cover colour: RAL 7035 -light grey
Gasket material: Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 120 °C
Temperature °C (continuous): -40 ... 80 °C
Temperature °F (short term): -40 ... 250 °F
Temperature °F (continuous): -40 ... 175 °F

Accessories:

MPS ARCA 4030 Mounting plate (350x250x2 mm)

Accessories:

MPP ARCA 3040 Mounting plate perforated (350x250x2 mm - 26x11 mm)
MPMP ARCA 4030 Mounting plate multiperforated (350x250x2 mm - □3.6 mm)
MPX ARCA 4030 Mounting plate (350x250 mm)
DRS ARCA 304015 DIN rail frame set
IDS ARCA 3040 Inner door set
PMK ARCA 40 Pole mounting kit
RCS ARCA 3040 Rain canopy set
SBK ARCA 30 Support bar kit
SBK ARCA 40 Support bar kit
DSP ARCA HLS Door stopper ARCA, horizontal, left, small
DSP ARCA HRS Door stopper ARCA, horizontal, right, small

Rating:

Ingress Protection (EN 60529): IP66
Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C: 960

Certificates:

SGS Fimko
Gost R

