

ARCA 406021



Sample photo

Order symbol: ARCA 406021
Product nbr: 8120026
Description: Cabinet, PC
Remarks: 2-point locking

EAN: 6418074079374
El. number:
Finland: 3423124
Electric No. 8212091249
Denmark:
Electric No. Sweden: 2500117

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:			Accessories:		
Length	Width	Height	MPP ARCA 4060	Mounting plate perforated (550x350x2 mm - 26x11 mm)	
mm:	400	600	210		
inch:	15.7	23.6	8.3	MPMP ARCA 6040	Mounting plate multiperforated (550x350x2 mm - □3.6 mm)
Materials:			MPX ARCA 6040	Mounting plate (550x350 mm)	
Material:	Polycarbonate		DRS ARCA 406021	DIN rail frame set	
Base colour:	RAL 7035 -light grey		IDS ARCA 4060	Inner door set	
Cover colour:	RAL 7035 -light grey		PMK ARCA 60	Pole mounting kit	
Gasket material:	Polyurethane		RCS ARCA 4060	Rain canopy set	
Temperatures:			SBK ARCA 40	Support bar kit	
Temperature °C (short term):	-40 ... 120 °C		SBK ARCA 60	Support bar kit	
Temperature °C (continuous):	-40 ... 80 °C		DSP ARCA HLS	Door stopper ARCA, horizontal, left, small	
Temperature °F (short term):	-40 ... 250 °F		DSP ARCA HRS	Door stopper ARCA, horizontal, right, small	
Temperature °F (continuous):	-40 ... 175 °F				
Accessories:			Rating:		
MPS ARCA 6040	Mounting plate (550x350x2 mm)		Ingress Protection (EN 60529): IP66		
			Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C		
			Electrical insulation: Totally insulated		
			Halogen free (DIN/VDE 0472, Part 815): 1		
			UV resistance: UL 508		
			Flammability Rating: UL 94 5VA		
			Glow Wire Test (IEC 695-2-1) °C: 960		

Rating:

Ingress Protection (EN 60529): IP66
Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C: 960

Certificates:

SGS Fimko
Gost R

