

ARCA 608030



Sample photo

Order symbol: ARCA 608030
Product nbr: 8120029
Description: Cabinet, PC
Remarks: 2-point locking

EAN: 6418074085160
El. number:
Finland: 3424064
Electric No. 8212095368
Denmark:
Electric No. Sweden: 2500121

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:				Accessories:	
	Length	Width	Height		
mm:	600	800	300	MPP ARCA 6080	Mounting plate perforated (730x530x2 mm - 26x11 mm)
inch:	23.6	31.5	11.8	MPMP ARCA 8060	Mounting plate multiperforated (730x530x2 mm - □3.6 mm)
Materials:					
Material:	Polycarbonate				
Base colour:	RAL 7035 -light grey				
Cover colour:	RAL 7035 -light grey				
Gasket material:	Polyurethane				
Temperatures:					
Temperature °C (short term):	-40 ... 120 °C				
Temperature °C (continuous):	-40 ... 80 °C				
Temperature °F (short term):	-40 ... 250 °F				
Temperature °F (continuous):	-40 ... 175 °F				
Accessories:					
MPS ARCA 8060	Mounting plate (730x530x2 mm)				
	MPX ARCA 8060 Mounting plate (730x530 mm)				
	IDS ARCA 6080 Inner door set				
	PMK ARCA 80 Pole mounting kit				
	RCS ARCA 6080 Rain canopy set				
	SBK ARCA 60 Support bar kit				
	SBK ARCA 80 Support bar kit				
	DSP ARCA LM Door stopper ARCA, left, midsize, for 5070-8060				
	DSP ARCA RM Door stopper ARCA, right, midsize for 5070-8060				
Rating:					
Ingress Protection (EN 60529): IP66					
Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C					
Electrical insulation: Totally insulated					
Halogen free (DIN/VDE 0472, Part 815): 1					
UV resistance: UL 508					
Flammability Rating: UL 94 5VA					
Glow Wire Test (IEC 695-2-1) °C: 960					

Certificates:

SGS Fimko

Gost R

