

ARCA 507030



Sample photo

Order symbol: ARCA 507030
Product nbr: 8120031
Description: Cabinet, PC
Remarks: 2-point locking

EAN: 6418074086006
El. number:
Finland: 3424062
Electric No. 8212095384
Denmark:
Electric No. Sweden: 2500119

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:			Accessories:		
Length	Width	Height			
mm:	500	700	300	MPP ARCA 5070	Mounting plate perforated (630x430x2 mm - 26x11 mm)
inch:	19.7	27.6	11.8	MPMP ARCA 7050	Mounting plate multiperforated (630x430x2 mm - □3.6 mm)
Materials:			MPX ARCA 7050	Mounting plate (630x430 mm)	
Material:	Polycarbonate		DRS ARCA 507030	DIN rail frame set	
Base colour:	RAL 7035 -light grey		IDS ARCA 5070	Inner door set	
Cover colour:	RAL 7035 -light grey		PMK ARCA 70	Pole mounting kit	
Gasket material:	Polyurethane		RCS ARCA 5070	Rain canopy set	
Temperatures:			SBK ARCA 50	Support bar kit	
Temperature °C (short term):	-40 ... 120 °C		SBK ARCA 70	Support bar kit	
Temperature °C (continuous):	-40 ... 80 °C		DSP ARCA LM	Door stopper ARCA, left, midsize, for 5070-8060	
Temperature °F (short term):	-40 ... 250 °F		DSP ARCA RM	Door stopper ARCA, right, midsize for 5070-8060	
Temperature °F (continuous):	-40 ... 175 °F		Rating:		
Accessories:			Ingress Protection (EN 60529): IP66		
MPS ARCA 7050	Mounting plate (630x430x2 mm)		Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C		
			Electrical insulation: Totally insulated		
			Halogen free (DIN/VDE 0472, Part 815): 1		
			UV resistance: UL 508		
			Flammability Rating: UL 94 5VA		
			Glow Wire Test (IEC 695-2-1) °C: 960		

Certificates:

SGS Fimko
Gost R

