

## 92x92x25mm (3.62x3.62x0.98in) - 7 blade



Bearing System— 2 Ball Bearing  
 Life Expectancy— Ball 70000hrs@ 25°C  
 Frame----- Thermoplastic PBT+30% GF, UL94-V0  
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0  
 Lead Wire----- UL 1007, AWG 24, 260±10mm, Red(+), Black(-)  
 Protection----- Locked rotor protection  
 IP Grade ----- Optional



Dim: 558x373x349 mm  
 N.W.: 14.4 kgs  
 G.W.: 17.6 kgs  
 Q'TY: 135 pcs



| FUNCTIONS | PART NUMBER      | RATED (VDC) | LABEL   |         | ACTUAL POWER (WATTS) | SPEED (RPM) | AIRFLOW       |                | PRESSURE |      | NOISE (dBA) | WEIGHT (Q'TY/CTN) |
|-----------|------------------|-------------|---------|---------|----------------------|-------------|---------------|----------------|----------|------|-------------|-------------------|
|           |                  |             | CURRENT | CURRENT |                      |             | (CFM)(m³/min) | (mmAq)(In H²O) |          |      |             |                   |
| 1b:AS     | C9225X12BPLPxy-7 | 12 (07~14)  | 0.350   | 0.350   | 4.20                 | 3600        | 66.94         | 1.90           | 6.01     | 0.24 | 41.16       | 106.5g (135pcs)   |
|           | C9225H12BPLPxy-7 |             | 0.230   | 0.220   | 2.64                 | 3000        | 55.78         | 1.58           | 4.18     | 0.16 | 35.73       |                   |
|           | C9225M12BPLPxy-7 |             | 0.180   | 0.135   | 1.62                 | 2600        | 48.34         | 1.37           | 3.14     | 0.12 | 31.99       |                   |
|           | C9225L12BPLPxy-7 |             | 0.140   | 0.108   | 1.30                 | 2200        | 40.91         | 1.16           | 2.25     | 0.09 | 27.56       |                   |
| 2a:FG     | C9225X24BPLPxy-7 | 24 (15~27)  | 0.220   | 0.180   | 4.32                 | 3600        | 66.94         | 1.90           | 6.01     | 0.24 | 41.16       | 106.5g (135pcs)   |
| 2b:RD     | C9225H24BPLPxy-7 |             | 0.150   | 0.120   | 2.88                 | 3000        | 55.78         | 1.58           | 4.18     | 0.16 | 35.73       |                   |
| 2c:RDb    | C9225M24BPLPxy-7 |             | 0.090   | 0.084   | 2.02                 | 2600        | 48.34         | 1.37           | 3.14     | 0.12 | 31.99       |                   |
|           | C9225L24BPLPxy-7 |             | 0.060   | 0.055   | 1.32                 | 2200        | 40.91         | 1.16           | 2.25     | 0.09 | 27.56       |                   |

