

92x92x38mm (3.62x3.62x1.50in) - 7 blade



Bearing System— 2 Ball Bearing
 Life Expectancy— Ball 70000hrs@ 25°C
 Frame----- Thermoplastic PBT+30% GF, UL94-V0
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0
 Lead Wire----- UL 1007, AWG 24, 260±10mm, Red(+), Black(-)
 Protection----- Locked rotor protection
 IP Grade ----- Optional



Dim: 553x339x245 mm
 N.W.: 13.5 kgs
 G.W.: 15.0 kgs
 Q'TY: 60 pcs



FUNCTIONS	PART NUMBER	RATED (VDC)	LABEL CURRENT	ACTUAL CURRENT	POWER (WATTS)	SPEED (RPM)	AIRFLOW (CFM)(m³/min)	PRESSURE (mmAq)(In H²O)	NOISE (dBA)	WEIGHT (Q'TY/CTN)
1b:AS	K9238H12BPLBxy-7	12 (08~14)	1.850	1.450	17.40	6500	132.94	3.76	22.88	225g (60pcs)
2a:FG	K9238M12BPLBxy-7		0.820	0.600	7.20	5000	102.26	2.90	13.54	
2b:RD	K9238L12BPLBxy-7		0.330	0.270	3.24	3500	71.58	2.03	6.63	
2c:RDb										
2d:LD	K9238X24BPLBxy-7	24 (15~27)	1.560	1.200	28.80	8000	163.61	4.63	34.65	225g (60pcs)
1a:IR	K9238H24BPLBxy-7		0.810	0.640	15.36	6500	132.94	3.76	22.88	
6:CL	K9238M24BPLBxy-7		0.430	0.310	7.44	5000	102.26	2.90	13.54	
3c:PPWM	K9238L24BPLBxy-7		0.170	0.140	3.36	3500	71.58	2.03	6.63	
3a:VPWM										
5a:TPWM	K9238X48BPLBxy-7	48 (36~57)	0.720	0.615	29.52	8000	163.61	4.63	34.65	225g (60pcs)
5b:RPWM	K9238H48BPLBxy-7		0.390	0.320	15.36	6500	132.94	3.76	22.88	
3b:IPWM	K9238M48BPLBxy-7		0.200	0.165	7.92	5000	102.26	2.90	13.54	
7a:CS	K9238L48BPLBxy-7		0.100	0.070	3.36	3500	71.58	2.03	6.63	

Remark:

- Part no. suffix: "xy"=Function detail or "x"=Function number, "y"=customer ID
- K series - Multifunction Extra High Performance.:**

Use a single coil differential type drive with the highest efficiency and the maximum airflow performance with the complete line of functions and with Airflow and Pressure higher than the P series.

