



Digital Earth Testers





UT520 series can perform precise 3-wire and simple 2-wire earth resistance measurement for power and electrical systems, lightning protection equipment, and ground system of all electrical equipment. This series is UNI-T' s introductory earth resistance tester with high economic value. Its light weight design is convenient for field work.

	Range	UT521	UT522	
Earth resistance (Ω)	0~20Ω	±(2%+10)		
	0~200Ω	±(2%+3)		
	0~2000Ω	±(2%+3)		
	0~40Ω		±(2%+20)	
	0~400Ω		±(2%+3)	
	0~4000Ω		±(2%+3)	
AC earth voltage (V)	0~200V	土(1%+4)		
	0~400V		±(1%+6)	
	Frequency: 50Hz/60Hz	√	√	
Features				
Display count		2000	4000	
Manual range		√	√	
Auto power off	Around 10 minutes	√	√	
Low battery indication		√	√	
Data hold		√	√	
Data storage		20	20	
LCD backlight		√	√	
Full icon display		√	√	
Double insulation protection		√	√	
Poor contact display	"Ω"	√	√	
Over-range display	Display "OL"	√	√	
Simple 2-wire testing		√	√	
Precise 3-wire testing		√	√	
Power	1.5V battery (LR6) x 6			
Display	70.6mm x 34mm			
Product color	Red and grey			
Product net weight	560g			
Product size	160mm x 100mm x 70.5mm			
Standard accessories	Batteries, simple test leads with alligator clips, standard test leads with alligator clips, earth spike, elastic strap			
Standard individual packing	Gift box, carrying bag, English manual			
Standard quantity per carton	8pcs			
Standard carton measurement	530mm x 300mm x 350mm			
Standard carton gross weight	19kg	19kg		