



## EDL-224ABC

Order No.: 0160100

### PRODUCTINFOS

#### PA A/B ceiling speaker,

with EN 54-24 certification. For systems with A/B speaker distribution. Cost-effective reduction of the required ceiling cutouts.

- 100 V transmission technology
- 2 separate speaker systems
- Full range speaker with a very high efficiency and high maximum volume level
- Metal housing
- Fire protection cover
- Quick mounting facility
- 3 power taps via push terminals
- Ball-proof according to DIN 18032, Part 3

#### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Konsul-Smidt-Str. 68  
28217 Bremen  
Germany

info@monacor.com

## TECHNICAL SPECIFICATIONS

### EDL-224ABC

Transmission technology	100 V
Frequency range	75-20,000 Hz
Power rating (RMS)	2 x 6/2 x 3/2 x 1.5 W
SPL	2 x 92 dB (1 W/1 m) 76 dB (EN, 1 W/4 m)
Max. rated SPL	2 x 100 dB (1 m) 85 dB (EN, 4 m)
Radiation angle, horizontal	180° (500 Hz) 180° (1 kHz) 160° (2 kHz) 80° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 180° (1 kHz) 160° (2 kHz) 80° (4 kHz)
Mounting cutout	Ø 230 mm
Mounting depth	110 mm
Dimensions	Ø 252 mm x 115 mm
Outside diameter	Ø 252 mm
Width	Ø 252 mm
Height	Ø 252 mm
Depth	115 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	1.84 kg
Packing unit	1
Type of speaker	2 x 100
Packaging dimensions (W x H x L)	0.28 x 0.13 x 0.28 m
Gross weight	2.02 kg
Net weight	1.84 kg

### EDL-224ABC

EAN code	4007754233353
Net weight	1.84 kg

