



PATL-100/XC

Order No.: 1000092

PRODUCTINFOS

100 V transformer,

for connecting a 100 V audio signal source to devices with line input.

- Adjustable line output level (0-5.6 V at 100 V input voltage), can be switched internally for other output voltages
- 100 V input with plug-in screw terminal
- Balanced XLR output, impedance: 1 k Ω , XLR panel plug
- RCA output
- Insulated plastic housing
- Galvanically isolated input and output
- Dimensions: 100 x 60 x 190 mm
- Weight: 625 g

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

PATL-100/XC

Description	100 V transformer
Output signal	0-5.6 V (at 100 V)
Admiss. ambient temp.	0-40 °C
Dimensions	100 x 60 x 190 mm
Weight	625 g
Inputs	plug-in screw terminal (100 V)
Outputs	XLR, bal. RCA

PATL-100/XC

EAN code	4007754275254
Net weight	0.625 kg