



PA-4040MPX

Order No.: 0173450

PRODUCTINFOS

4-zone mixer,

for general multi-room PA applications.

- 4 zones with user-defined routing of all input channels
- 3 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control and zone routing switch
- Microphone inputs with 15 V phantom power, to be activated as required
- Priority function for channel 1, switchable
- Independent paging input, can be routed to each zone
- 4 zone outputs, can be adjusted individually
- Connection for monitor speaker
- Level control via VU meters for zone and monitor
- Adjustable headphone output
- Mains operation or 24 V emergency power operation

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

Warning and Safety Instructions

The device is supplied with dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Risk of electric shock!

Do not use this device and disconnect it immediately from the power supply if the device or the power supply cable is visibly damaged, if a defect might have occurred after the device was dropped or suffered a similar accident, if malfunctions occur. Any repairs must be carried out by specialists.

The product is suitable for indoor use only. Protect it against dripping water, splash water and high air humidity (admissible ambient temperature range is 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated in the device must be dissipated by air circulation. Never cover the air vents of the housing.

If the device is to be put out of operation definitely, dispose of the product in accordance with local regulations.

TECHNICAL SPECIFICATIONS

PA-4040MPX

Channels	5
Zones	4
Inputs	5 mV/4 k Ω , 100 mV/10 k Ω (mic/line), 100 mV/30 k Ω (line)
Frequency range	50-17,000 Hz
Equalizer bass	\pm 10 dB/100 Hz
Equalizer treble	\pm 10 dB/10 kHz
S/N ratio	> 65 dB (mic), > 75 dB (line)
THD	< 1%
Phantom power	15 V
Power supply	\sim 230 V/50 Hz/20 VA, DC 24 V/600 mA
Mains voltage	\sim 230 V
Mains frequency	50 Hz
Power consumption, operation	20 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 600 mA
Admiss. ambient temp.	0-40 °C
Width	482 mm

PA-4040MPX

Height	133 mm
Depth	220 mm
Rack units, RU	3
Weight	4.5 kg
Connections	3 x combo 6.3 mm/XLR (mic/line), 2 x RCA L/R (line), 4 x plug-in screw terminal (zones), screw contacts (monitor speakers), screw contacts (mix out), screw contacts (paging), screw contacts (priority)
Packaging dimensions (W x H x L)	0.28 x 0.22 x 0.57 m
Gross weight	5.68 kg
Net weight	4.7 kg

PA-4040MPX

EAN code	4007754225808
Net weight	4.7 kg