

80x80x38mm (3.15x3.15x1.5in) - 7 blade



Bearing System— 2 Ball Bearing
 Life Expectancy— Ball 70000hrs@ 25°C
 Frame----- Thermoplastic PBT+30% GF, UL94-V0
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0
 Lead Wire----- UL 1007, AWG 24, 260±10mm, Red(+), Black(-)
 Protection----- Locked rotor protection
 IP Grade ----- Optional



Dim: 493x339x218mm
 N.W.: 12.0 kgs
 G.W.: 13.5 kgs
 Q'TY: 60 pcs

FUNCTIONS	PART NUMBER	RATED	LABEL	ACTUAL	POWER	SPEED	AIRFLOW	PRESSURE	NOISE	WEIGHT		
		(VDC)	CURRENT	CURRENT	(WATTS)	(RPM)	(CFM)(m³/min)	(mmAq)(In H²O)	(dBA)	(Q'TY/CTN)		
1b:AS 2a:FG 2b:RD 2c:RDb 6:CL	R8038H12BPLBxy-7	12 (07~14)	1.430	1.200	14.40	7000	98.47	2.79	27.23	1.07	57.10	200g (60pcs)
	R8038M12BPLBxy-7		0.720	0.500	6.00	5500	77.37	2.19	16.81	0.66	50.80	
	R8038L12BPLBxy-7		0.330	0.293	3.52	4000	56.27	1.59	8.89	0.35	42.50	
	R8038H24BPLBxy-7	24 (15~27)	0.650	0.500	12.00	7000	98.47	2.79	27.23	1.07	57.10	200g (60pcs)
	R8038M24BPLBxy-7		0.340	0.270	6.48	5500	77.37	2.19	16.81	0.66	50.80	
	R8038L24BPLBxy-7		0.170	0.160	3.84	4000	56.27	1.59	8.89	0.35	42.50	
	R8038H48BPLBxy-7	48 (36~57)	0.330	0.293	14.06	7000	98.47	2.79	27.23	1.07	57.10	200g (60pcs)
	R8038M48BPLBxy-7		0.200	0.140	6.72	5500	77.37	2.19	16.81	0.66	50.80	
	R8038L48BPLBxy-7		0.100	0.093	4.46	4000	56.27	1.59	8.89	0.35	42.50	

